



07

Date: November 10, 2016

NOTICE INVITING TENDER

Shyam Lal College (University of Delhi), G.T Road Shahdara, Delhi-110032, Invites sealed quotations for Aluminium Portion work in shyam Lal college.

Followings are the Specifications.

SN.	DESCRIPTION	QUANTITY (Approx)	RS./UNIT	AMOUNT
A. 1.	<p><u>PARTITION WORK</u></p> <p><u>FIXED ALUMINIUM PARTITION</u></p> <p>Providing and Fixing Aluminium Partition consisting of Aluminium Sections 63.50 MM X 38.10 MM X 1.50 MM thick hollow anodised of Jindal / Hindalco make conforming to IS 733 and IS 1285. The anodizing shall be transparent and complying IS 1868 (minimum anodic coating of grade AC 15). The Sections would be installed at an interval of 900 MM vertically and bottom section of size 114.60 x 44.45 x 1.50 MM Aluminium snap beeding for glazing/panelling etc. and 5.5 MM thick float Transparent Glass including providing screw less aluminium glazing clip. Bottom upto 900 MM Height Will be provided with 12 MM thick pre-laminated particle board conforming to IS 12823 Grade I type II of Bhutan / Nepal / Greenlami of interior grade complete with fixing clips, fasteners, filling up of gaps at junction, top, bottom, & sides with required PVC/Nepprene felt etc. The joints shall be smooth, mitred and jointed with cleat angle etc as per direction of engineer/site Incharge.</p> <p><u>ALUMINIUM DOORS & FRAME</u></p> <p>Providing and Fixing anodised Aluminium Door consisting of Sections 83.5 MM X 44.45 MM X 1.5 MM thick vertical, top and middle horizontal members and bottom members of size 114.60 MM X 44.45 MM X 1.5 MM thickness. Bottom upto 915 MM will be provided with 12 MM thick pre-laminated board as mentioned in the item 1 above and rest above provided with 5.5 MM thick transparent float glass. Door provided with</p>	40.00 Sqmt		
		8.00 Sqmt.		



	100 MM brass dead lock Godrej make, hydraulic floor spring,(double action) heavy quality ISI marked with SS cover plate 100 MM dia Circular plate type handles (2 nos.) tower bolt of size 250 x10 mm (Barrel Type) including cutting the floor etc complete as directed by engineer/site In charge.			
2.	<u>WHITE WASHING</u> P/A Distempering with First quality acrylic distemper (Ready mix) of approved brand and manufacture (two or more coats) of required shade on wall and ceiling after fill up all the patches & repairs, colour including. (Rate inclusive of lift to all levels & heights.)	70.00 Sqmt		
3.	<u>PAINTING & POLISHING</u> P/A Painting with synthetic enamel paint of approved brand and manufacture of required color to give an even shade. (Rate inclusive of lift to all levels & heights.)	10.00 Sqmt		
B.	<u>ELECTRICAL WORK</u>			
1.	<u>WIRING & POINTS</u> Supply and wiring for light, fan, exhaust fan, 6A socket, points etc. with 6A switch controlled using 1.5 sq mm stranded copper conductor PVC insulated 1100 volt grade wires from switch control boxes to point in surface / concealed heavy duty PVC conduit / 25mm x 25mm x 3mm thickness / heavy duty PVC batten including M.S. / G.I. boxes, together with wiring accessories such as 6A / 16A modular type switches, sockets in boxes of suitable size including circuit wiring from DB to switch board with 2.5 sq mm PVC insulated copper conductor (only one circuit of 2.5sq mm wires is to be laid from DB to switch board and from switch board to switch board) along with one run of 1.5 Sq mm PVC insulated copper earth wire, PVC bushes for conduit ends, chrome - plated brass screws, identification ferrules at either ends			



SHYAM LAL COLLEGE
(University of Delhi)
G.T. Road, Shahdara, Delhi-32
Website: www.shyamlal.du.ac.in

complete in all respect. (The circuit wiring shall not be paid extra). Maximum 8 nos. of light points shall be connected in the circuit. (Measurement of length is from switch board to light / equipment fitting). <ul style="list-style-type: none">• Single light point controlled by a 6Amps modular type switch.• Ceiling fan point control by 1 No. 6 amp. Switch but without regulator• Switch socket points 6 Amp.• Switch socket points 16 Amp.	10 Nos.		
	8 Nos		
	8 Nos		
	4 Nos		

1. Rates are to be sent in sealed envelope from Bidders shall be addressed to the **Principal, Shyam Lal College** (University of Delhi), G.T. Road, Shahdara, Delhi-110032.
2. The work should be completed within **10 days** from the date of award of the contract.
3. The college will not be responsible for late receipt of any tender (i.e. after due date) the same will not be entertained. The tender will be accepted upto **4:00 pm** on or before **18/11/2016**.
4. No advance payment will be made.
5. If any additional charges related to taxes should be mentioned separately or otherwise the total amount will be treated as all inclusive.
6. College reserves the right to accept or reject any or all the tender(s) in full or part without assigning any reason. The decision of the college in this regard shall be final and binding on all. It shall not be obligatory on the part of the College to accept the lowest tender and no explanation shall be given with regard to reason for rejection of tender.
7. The work will be done as per the on-site instruction under the supervision of a College Authorities.
8. The material supplied must conform to the relevant IS Specifications.
9. The payment will be made as per the measurement and verification of the quality of work by the competent agency / person.
10. Appropriate penalty will be imposed in case of inferior workmanship. The materials brought to site would be got checked before installation & utilisation.
11. White washing & Enamel paints colour & make decided by college Authorities.
12. The quantity is approximate so 10% quantity is increase and decrease as per requirements.
13. Design of aluminum partition work will be decided by College Authorities.

The quotation must be addressed to the Principal, Shyam Lal College and the envelope must be superscribed "Sealed Quotation ".

S/d
Principal

S/d
Principal (Eve.)